


图片	序号	型号	附件编号	名称	选配机型	用途
	1	DK-W.01	B-W-0500000	万能夹具量尺 Caliper	轮胎平衡机 Wheel balancer	与万能夹具配套使用 Match with Universal adaptor to use
	2	B-W.02	B-W-1000000	万能夹具 Universal adaptor	W61/W61B W62/W62B 36轴 Φ36 balancer shaft	平衡无中心孔轮辋时使用，有三等分、四等分、五等份组合形式，用量尺直接测量中心孔的间距可用来调节夹具的夹爪的相对位置 直径95~280 Balance the tyre without the center hole. Adjust the relative position of the jaw by directly measure the hole distnace. ΦMin.~ΦMax.=Φ95~Φ280
	3	B-W.04	B-W-5000000	万能夹具 Universal adaptor	W90/W91/W92/W95/W95H /W96/W60H/MW620/MW620H 40轴 Φ40 balancer shaft	
	4	B-W.05	B-W-9000000	二次万能夹具 Universal adaptor	所有Φ40轴平衡机 Suitable for all the wheel balancers with Φ40 balancer shaft	
	5	SK-A	TB-SK-0000002	四孔夹具 Four-hole adaptor	所有平衡机(Φ40轴) Fit all the wheel balancers with Φ40 balancer shaft	针对于固定孔数为5的轮辋。解决二次拆装过大问题.Φ98.Φ100.Φ108.Φ112.Φ120.65.Φ130.Φ139.7 For the rim with 5 holes to slove big unbalance weight when 2nd-mount. Φ98.Φ100.Φ108.Φ112.Φ120.65.Φ130.Φ139.7 特制夹具，为特殊的无中心孔的四孔轮辋设计。 Custom clamps designed for special four-hole rims without center holes.
	6	SK-B	TB-SK-0000001	四孔夹具 Four-hole adaptor	所有平衡机(Φ36轴) Fit all the wheel balancers with Φ36 balancer shaft	
 	7	MJ-I	TB-M-0410000	平衡轴组件总成 Motorcycle Adaptor	轮胎平衡机 wheel balancer	摩托车轮胎专用锁紧轴，配有测量延长尺，适用于无轴承的摩托车轮胎，锥体尺寸为22mm-50mm，轴粗19mm Special lock shaft with extend scale for motorcycle tyre without bearing; cones size:22mm-50mm, with adapter shaft rod diameter 19mm
			TB-M-0130000			
	8	MJ-I-2	TB-M-0320000	平衡轴组件总成 Motorcycle Adaptor	轮胎平衡机 wheel balancer	摩托车轮胎专用锁紧轴，配有测量延长尺，适用于无轴承的摩托车轮胎，锥体尺寸为11mm-20mm，轴粗10mm Special lock shaft with extend scale for motorcycle tyre without bearing, cone size 11mm—20mm，with adaptor shaft rod diameter 10mm
	9	MJ-I-3	TB-M-0310000	平衡轴组件总成 Motorcycle Adaptor	轮胎平衡机 wheel balancer	摩托车轮胎专用锁紧轴，配有测量延长尺，适用于无轴承的摩托车轮胎，锥体尺寸为10.5mm-20mm，轴粗9.5mm Special lock shaft with extend scale for motorcycle tyre without bearing, cone size, 10.5mm—20mm,with adapter shaft rod diameter 9.5mm
	10	MJ-I-4	TB-M-0210000	平衡轴组件总成Φ40 Motorcycle Adaptor Φ40	轮胎平衡机 wheel balancer	摩托车轮胎专用锁紧轴，配有测量延长尺，适用于无轴承的摩托车轮胎，锥体尺寸为13mm-24mm，轴粗12mm special lock shaft with extend scale for motorcycle tyre without bearing, cone size, 13mm-24mm,with adaptor shaft rod diameter 12mm
	11	MJ-I-5	TB-M-0110000	平衡轴组件总成Φ40 Motorcycle Adaptor Φ40	轮胎平衡机 wheel balancer	摩托车轮胎专用锁紧轴，配有测量延长尺，适用于无轴承的摩托车轮胎，锥体尺寸为15mm-35mm，轴粗14mm special lock shaft with extend scale for motorcycle tyre without bearing, cone size, 15mm—35mm,with adaptor shaft rod diameter 14mm

图片	序号	型号	附件编号	名称	选配机型	用途
	12	MJ-II	TB-M-0100000	平衡机摩托车夹具 Motorcycle Adaptor	W61/W61B/W62/W62B 36轴 Φ36 balancer shaft	平衡轴用摩托车轮胎专用夹具，配有测量延长尺，适用于带有轴承的摩托车轮胎，锥体尺寸为16mm-35mm special lock shaft with extend scale for motorcycle tyre with bearing; cones size:16mm-35mm
	13	MJ-II-2	TB-M-0900000	平衡机摩托车夹具 Motorcycle Adaptor	W90/W91/W92/W95 /W95H/W96 40轴 Φ40 balancer shaft	
	14	MJ-II-3	TB-M-0900000A	平衡机摩托车夹具 Motorcycle Adaptor	W60H/MW620/MW620H 40轴 Φ40 balancer shaft	
	15	BJ-01	TB-J-0100000	平衡机升降车 Tyre lift	轮胎平衡机 Wheel balancer	举升小车,最大举升重量:300KG,举升高度:335mm 辅助提升轮胎至平衡轴，节省人力，配备移动转轮。 Assist to lift the tyre to the shaft to save the man power. Max. lift weight: 300KG. Lifting height :335mm
	16	BJ-205	WD-2023001	平衡机升降车 Tyre lift	轮胎平衡机 Wheel balancer	举升小车 最大举升重量75KG 举升高度520mm 辅助提升轮胎至平衡轴，节省人力，配备椎体挂柄。 包装尺寸：860*480*410mm 净重52.7kg Assist to lift the tyre to the shaft to save the man power. Max. lift weight: 75KG. Lifting height :520mm; Package size: 860*480*410mm; Net weight52.7kg
	17	BJ-206	WD-2023002	平衡机升降车 Tyre lift	轮胎平衡机 Wheel balancer	举升小车 最大举升重量80KG 举升高度520mm 包装尺寸：840*590*410mm 毛重：53.5kg Assist to lift the tyre to the shaft to save the man power. Max. lift weight: 80KG. And the lift height is 520mm. Package size：840*590*410mm Gross weight53.5kg
	18	B-W.06	B-W-0600000	无孔夹具 Adapter handa assembly	W69/W69B W70/W70B	平衡轴与轮胎固定工具 centering adapter for truck wheel
	19	B-W.07	B-W-0900000	无孔夹具 Adapter handa assembly	W99	
	20	B-P.01	TB-P-0100018	36轴特大锥体 Φ36 exlarge cone	W61/W61B/W62/W62B 36轴 Φ36 balancer shaft	适合大中心孔轮胎平衡时装夹锥体范围Φ95- Φ175 Compatible to mount the wheels with large central hole. Cone size: Φ95-Φ175
	21	B-P.02	TB-P-0300015	40轴特大锥体 Φ40 exlarge cone	W90/W91/W92/W95/W95H /W96/W60H/MW620/MW620H 40轴 Φ40 balancer shaft	适合大中心孔轮胎平衡时装夹 锥体范围Φ95- Φ175 Compatible to mount the wheels with large central hole. Cone size:Φ95-Φ175
	22	B-P.03	TB-P-0200010 GB70·1-1985-M8×20	法兰盘 Large flange	轮胎平衡机 wheel balancer	用于轮辋安装面大于平衡轴法兰直径尺寸的轮辋,适用轮辋中心孔188mm---232mm Compatible to mount the wheels with large central hole with size 188mm—232mm
	23	BT-X-01	BT-X-1000000	辅助定位激光灯 Laser light	轮胎平衡机 wheel balancer	用于在进行动平衡操作时候 铅块位置的辅助定位 assist to locate the position when stick the weight
	24	B-K.01	TB-K-0200000HWK	哈维克快速螺母 Haweka lock nut	W90/W91/W92/W95/W95H /W96/W60H/MW620/MW620H 40轴 Φ40 balancer shaft	用于平衡机锁定轮胎 for locking wheel on the balancer